DSP Analog Inputs

Item	Part Number	Description
	39001 MX202-K	Shure Ceiling Microphone & Mount Kit
	41021 CM16WS	Biamp Shotgun Supercardoid Ceiling Mount Microphone – For use in applications where narrow audio pickup is required
	42007 MX393C	Shure Desktop boundary Microphone – Microphone has push to talk membrane switch – For use in control room applications or in clinic rooms where a hard-wired desktop microphone is required.
	39007 GNMIC-K	Tabletop Gooseneck Push-to-Talk Microphone

DSP Analog Outputs

Item	Part Number	Description
	39071 CSPKR-K	6.5 Inch 2-Way in-Ceiling Speaker with Bluetooth 5.0 Stereo Audio Amplifier Receiver
	39060 ORAS-K	Observation Room Audio Solution: 1 speaker, and 1 stereo head phone amp with volume knob used for live audio when one way glass is used for live observation (Utilizes 1 output on the DSP)
	39025 DBPSP1-K	Flush Mount Speaker with Volume Control, 24VDC Power Supply & Wall Mount Kit
	39026 DBSHIM-K	Flush Mount Headphone Jack with Amplifier Volume Control, 24VDC Power Supply & Wall Mount Kit for monitoring audio in interview / clinic rooms

DSP IP Inputs

Item	Part Number	Description
	41022 TCMXA	AVB Beam tracking Low Profile Microphone (includes speaker 2 amplifier outputs – typically 1 output for camera and 1 output for 41023 Desono speaker.)
	40125 AMP450	Tesira AMP-450BP - The Tesira AMP-450BP is an AVB/TSN enabled, four-channel PoE+ conferencing amplifier for use with the Desono C-IC6 ceiling speaker (Supports up to 4 rooms using the Desono Speaker.)
	41023 DSPKR	The Desono C-IC6 is a low-profile, two-way passive coaxial loudspeaker optimized for speech reproduction in conferencing applications. Ceiling mount only.